

**DOUBLENUT<sup>®</sup>**

**HAYSTIX<sup>®</sup>**

**PRO-Link<sup>®</sup>**

P: 855-361-5987  
F: 855-818-8865  
sales@pro-link.us



**HAYSTIX<sup>®</sup>** are a premium line of hay spear products, their quality, and design ranks them among the top spears in the world! HAYSTIX products compete well with spears from Norway, Germany, and Italy and are a popular choice for dealers, OEM, and welding shops. Tapered HAYSTIX only come in Conus I (1.375"), and Conus II (1.75"). Crosshole HAYSTIX include part number for both 1.625" and 1.75", and associated hardware.

**HAYSTIX<sup>®</sup>** are rigorously tested to accurately determine performance.

- All standard spears are rated on a 30" load center.
- 1 3/4" spears are rated for 3,500 lbs.
- **1 5/8" spears are rated for 3,000 lbs.**
- **Based on a typical 5x6 round bale, tests for deflection and deformity indicate 100% return after load.**
- Fatigue testing to 30,000+ ensures durability and long life.
- **Thread and nut union are configured to reduce unexpected failures when installed correctly.**

The **HAYSTIX<sup>®</sup>** **DOUBLENUT<sup>®</sup>** spear employs a jam nut with the conical nut on all tapered HAYSTIX<sup>®</sup> products. Incorporating the jam nut keeps the conical nut tight to the sleeve, **eliminating flex inside the sleeve. This effectively reduces the most common spear failures, and thread breakage issues.**



Bracketed HAYSTIX



Crosshole HAYSTIX



Tapered HAYSTIX

Crosshole HAYSTIX:

- 48BX - 1.625" X 48" crosshole stix, 155BU bracket with gusset, 12X3 bolt and locknut, 3,000 lb. capacity.**
- 55SX - 1.75" X 55" crosshole stix, 175 sleeve, 12X3 bolt and locknut, 3,500 lb. capacity.**
- 49SX - 1.75" X 49" crosshole stix, 175 sleeve, 12X3 bolt and locknut, 3,500 lb. capacity.**
- 48SX - 1.625" X 48" crosshole stix, 155 sleeve, 12X3 bolt and locknut, 3,000 lb. capacity.**
- 39SX - 1.625" X 39" crosshole stix, 155 sleeve, 12X3 bolt and locknut, 3,000 lb. capacity.**

Tapered HAYSTIX:

- 55TXJ - 1.75" X 55" tapered stix, 144T sleeve, M30, JN15 Nuts, 3,500 lb. capacity.**
- 49TXJ - 1.75" X 49" tapered stix, 144T sleeve, M30, JN15 Nuts, 3,500 lb. capacity.**
- 43TXJ - 1.75" X 43" tapered stix, 144T sleeve, M30, JN15 Nuts, 3,500 lb. capacity.**
- 39TXJ - 1.75" X 39" tapered stix, 144T sleeve, M30, JN15 Nuts, 3,500 lb. capacity.**
- 33TXJ - 1.75" X 33" tapered stix, 144T sleeve, M30, JN15 Nuts, 3,500 lb. capacity.**

**Multi-Purpose Haystix:**

- 436TXJ - 1.375" X 43" tapered stix, 110T sleeve, M24, JN12 Nuts, 1,700 lb. capacity.**
- 396TXJ - 1.375" X 39" tapered stix, 110T sleeve, M24, JN12 Nuts, 1,700 lb. capacity.**
- 336TXJ - 1.375" X 33" tapered stix, 110T sleeve, M24, JN12 Nuts, 1,700 lb. capacity.**

Hardware:

- 175BU - 1.75" ID Square Bracket w/ 3" Ubolts**
- 175 - 1.75" ID X 5.75" Crosshole sleeve**
- 144T - 1.75" ID X 5.75" Tapered sleeve**
- 180 - 1.75" ID X 2" OD X 5" bushing**
- M30 - Conical nut 30 X 2.0 Metric
- 58X3U - .625" X 3" Ubolt assembly**

- 155BU - 1.625" ID Gusseted Bracket w/3" Ubolts**
- 155 - 1.625" ID X 6" Crosshole sleeve**
- 110T - 1.375" ID X 4.25" Tapered sleeve**
- 112 - 1.625" ID X 2" OD X 4.25" bushing**
- JN15 - Jam nut 30 X 2.0 Metric
- Stab1 - Stabilizer Assy. w/ spear,sleeve, and bolt**

